Atrust Mobile Thin Client
mt100

1 **Internal Microphone**
Built-in microphone for audio input.

2 **Power Button / Power LED**
Press to turn on the client / Indicates the status of power.

3 **Keyboard**
Built-in keyboard for control and input.

4 **Touch Pad**
Built-in pointing device for control and input.

5 **Speakers**
Built-in speaker for audio output.

6 **DC IN**
Connects to an AC adaptor.

7 **VGA Port**
Connects to an external display.

8 **LAN Port**
Connects to a host server through a LAN switch.

9 **USB Port**
Connects to a USB device.

10 **Microphone / Headphone Port**
Connects to a microphone / a set of headphonse or a speaker system.

11 **USB Port**
Connects to a USB device.

12 **Smartcard Reader (Optional)**
Insert a smart card for identification, authentication.

13 **Kensington Lock Slot**
Connects a Kensington cable to secure the mobile thin client.

Atrust mt100 Features

- **Low total cost of ownership**
  Additional computing access is as simple as adding more thin client devices. The total cost of ownership is then drastically reduced.
- **Simple click and play**
  mt100 connects to the host server with a Remote Desktop connection. Just click the shortcut for a Remote Desktop session, you can immediately start a session and enjoy the computing resources.
- **Rich remote user experience**
  With Citrix HDX/ICA, Microsoft RDP and VMware View, mt100 can provide a rich and efficient computing experience.
- **Easy management and maintenance**
  Since all computing tasks are mainly performed on a server, all hardware and software issues are significantly reduced on the client side. All user management, software installations, system management, and upgrades are done on a single server.

Atrust mt100 Mobile Thin Client

System	
Processor	TI ARM 1.0 GHz
Memory	
System memory	2GB
Flash memory	4GB
Display	
LCD Type/Resolution	14" 16:9 Glare / 1366 x 768 pixel, LED Backlight
I/O Interfaces	
I/O ports	1 x RJ-45, 1 x Headphone port, 1 x Microphone port, 1 x DC IN, 3 x USB, 1 x VGA, 1 x Built-in microphone, 1 x Smart card slot (optional), Internal speaker
Networking	
Ethernet	10/100/1000Mb
Wireless	IEEE 802.11a/b/g/n
Keyboard	Keyboard 87 keys
Touch Pad	Glide, 2 buttons
Dimensions / Weight	
Dimensions	(W) 339 x (D) 239.4 x (H) 25.4 mm
Weight	1.68kg
Environment	
Operating temperature	0˚C ~ 35˚C
Non-operating temperature	-30˚C ~ 60˚C
Operating humidity (Rh)	10% ~ 90% (non-condensing)
Non-operating humidity (Rh)	5% ~ 95%
AC Adaptor	
Operating voltage range	100 ~ 240 VAC
Rated line frequency	50 ~ 60 Hz
AC Adaptor	19V, 65W, 3.42A
Battery capacity	5900 mAh, 65Wh (Battery Pack)
Protocols	
Protocols	Citrix ICA/HDX, Microsoft RDP with RemoteFX, VMware Horizon View

© 2013 Atrust Computer Corp. The information contained herein is subject to change without notice. Atrust shall not be liable for technical or editorial errors or omissions contained herein.To learn more, visit www.Atrustcorp.com.

Atrust Computer Corp.
3F, 361 Fusing 1st Rd., Gueishan, Taoyuan County 333, Taiwan
T.+886-3-3288837 F.+886-3-3288973
sales@atrustcorp.com www.atrustcorp.com